

A&M
Truck Parts
LIMITED

THE WEATHER-TITE™ M2 LIFTGATE ASSEMBLY

THE ONLY DUAL POLE PLUG CONNECTION WITH
SUPERIOR CORROSION PROTECTION



AVOID DOWNTIME DUE TO CORROSION AND KEEP
YOUR LIFTGATE CYCLING FOR ON-TIME DELIVERIES.



Heavy Duty Jacketing

Flexible from - 82°F to 195°F (- 63°C to 91°C)
with chemical and abrasion resistance

Weather-Proof Plug

Unbreakable, non-corrosive housing
which is completely molded to the
electrical cable to combat against
corrosion



Moisture Blocking Seal

The WEATHER-TITE™ seal adds additional
corrosion protection at the front of the plug
by blocking moisture and contaminants from
entering the electrical system through the
coupled connection



Common Standard Connection

Will work with any standard J3082
dual pole liftgate socket



WE MAKE PRODUCTS THAT MAKE A DIFFERENCE®

2495 Meadowpine Blvd, Unit #3, Mississauga ON

☎ 800-814-1975

 **PHILIPS**

WEATHER-TITE™ M2 Liftgate Assemblies

- For dual pole liftgate applications utilizing a trailer battery pack
- Features plugs that are unbreakable with non-corrosive housing which are completely molded to the electrical cable to combat against corrosion
- The WEATHER-TITE™ seal adds additional corrosion protection at the front of the plug by blocking moisture and contaminants from entering the electrical system through the coupled connection
- 100 amp continuous capacity, 200 amp intermittent capacity
- Flexible from - 82°F to 195°F (- 63°C to 91°C)
- Meets J3082 standards

COILED DUAL POLE WEATHER-TITE™ M2 - 4 GA.



2/4 ga. Fine Stranded Copper

23-23276 12', 1 ground, 1 hot, 4 ga.

23-26276 15', 1 ground, 1 hot, 4 ga.

23-29276 15' with 48" lead, 1 ground, 1 hot, 4 ga.

- Excellent recoil memory, chemical and abrasion resistance

COILED DUAL POLE WEATHER-TITE™ M2 - 2 GA.



2/2 ga. Fine Stranded Copper

25-23276 12', 1 ground, 1 hot, 2 ga.

25-26276 15', 1 ground, 1 hot, 2 ga.

25-29276 15' with 48" lead, 1 ground, 1 hot, 2 ga.

- Excellent recoil memory, chemical and abrasion resistance

STRAIGHT DUAL POLE WEATHER-TITE™ M2 - 4 GA.



2/4 ga. Fine Stranded Copper

23-22576 12', 1 ground, 1 hot, 4 ga.

23-22776 15', 1 ground, 1 hot, 4 ga.

- Good chemical and abrasion resistance

STRAIGHT DUAL POLE WEATHER-TITE™ M2 - 2 GA.



2/2 ga. Fine Stranded Copper

25-22576 12', 1 ground, 1 hot, 2 ga.

25-22776 15', 1 ground, 1 hot, 2 ga.

- Good chemical and abrasion resistance

WE MAKE PRODUCTS THAT MAKE A DIFFERENCE®

2495 Meadowpine Blvd, Unit #3, Mississauga ON

☎ 800-814-1975

